

Urinal EDU-1

Art. no. EDU-1
GTIN 7393069022759



Description


Urinal for wall mounting. Supplied with vandal resistant cover for concealed fixing, grated waste, spreader, fixing bracket and flexible tube for easy water connection.

Overall dimension in mm	330 x 500 x 414
Material	AISI 304
Material thickness in mm	1,6
Installation height in mm	962
Gross weight in kg	9.50
Weight, pallet	172.20
Pcs per pallet	16

Installation

Fasten the fixing bracket to the wall, and hang the urinal. Connect water in- and outlet. Fix the screws on the lower part of the urinal.

Recommended height is 700mm from floor to the lower edge.



Installation EDU-1

ASSEMBLY:


Included in the box:

- * Urinal with fitted flush system and effluent valve
- * Suspension bar
- * Assembly kit
- * Key to jet nozzle: hexagon with hole

Ensure that all parts are contained in the pack before assembly begins.

Mount the mounting rail onto the wall and hang the urinal on it. Connect to the water and outlet. Affix the product's bottom edge to the wall or frame through the welded mounting bracket. Screws and plugs are supplied with the product.

Recommended mounting height: 700 mm from the floor to the front of the urinal pool for use by adults. Lower if it is mainly children who will use it.



Maintenance EDU-1

SPARE PARTS:

Front part of spray head: 78085

Hexagonal key with holes: 86144

Nipple projection for spray head: ZNIPPLE

Flexible hose: 82045

The spray head can be cleaned by removing the front piece and removing scale and other debris without the water having to be closed off.

MAINTENANCE:

INTRA PRODUCTS OF STAINLESS STEEL

Several of our products are delivered entirely or partly covered with plastic wrapping. This wrapping protects the products during transport. This wrapping must be removed before using the products.

In order for your Intra stainless steel product AISI304 to retain its original quality and appearance we recommend regular cleaning. Use mild soap or cleaning products specifically designed for stainless steel and clean water. Then wipe the surface with a dry cloth.

Never use detergents containing chlorine, iodine, fluoride or abrasives on stainless steel. Also avoid contact with acid solutions and other substances

incompatible with stainless steel.

Remember that food and skin care products may contain such substances, e.g. ketchup, juice, salt, certain cleansers, nail polish, etc. Promptly remove spills of such products.

Observe the following:

- * Do not allow water or other liquid to dry in. This is to avoid staining the surface.
- * Even though stainless steel can withstand harsh treatment, it can easily be scratched by sharp objects. For products with normal, polished (brushed) finish, this will be very visible when the product is new, but after a period of use, this will be negated as the steel loses its lustre. For products with satin and polished finishes, the scratches will always be visible. Never use scouring powder or steel wool on stainless steel. In addition to scratching the steel, wire wool will leave behind small particles that may develop into rust spots which, over time, may corrode the steel.
- * Stainless steel must not come into contact with, or be in environments containing, chlorine solutions for long periods of time.
- * Silver polish causes stains which cannot be removed.