

# Wash trough P12NFOL

**Art. no.** P12NFOL  
**GTIN** 7393069021721



<b>Overall dimension in mm</b>	1200 x 430 x 140
<b>Bowl dim. in mm</b>	1130 x 300 x 140
<b>Cut-out dimension, inset model</b>	408 x 1178
<b>Material</b>	AISI 304
<b>Material thickness in mm</b>	0,9
<b>Installation height in mm</b>	900/ 700/ 500

## Description

P12NFOL is a fully pressed stainless steel washing trough for insertion into boards. The sink is designed to be mounted over cabinets which utilise space under the washing trough. Supplied with overflow and 1 1/2" effluent valve with dome grate. Cabinet solution under the sink not included.



# Installation P12NFOL

## ASSEMBLY:

Included in the box:

- \* The washing troughs
- \* Overflow pipe 50cm
- \* Valve 1 1/2 with dome grate and overflow
- \* Gasket bottom section 1 1/4" and 1 1/2"
- \* Overflow - T MacAlpine
- \* Rosette for overflow T
- \* Gasket for overflow T
- \* Dome grate
- \* Screws M6

Ensure that you have all the parts before assembly begins.

Cut a hole in the countertop. Mount the valve and overflow- and possibly also mixer taps. Glue the washing trough in place and apply weight to the washing trough so that it is pressed against the countertop all the way around the flange and makes good contact.

Connect the drain.

## SPARE PARTS:

Valve dome grate 1 1/2" with dome grill overflow:: 79144

Overflow pipe 50 cm: 79027

Gasket bottom section 1 1/4" and 1 1/2" 79030

Overflow rosette: 79032

Overflow T: 79026

Gasket overflow T: 79034

Depth in mm 140

Measure basin in mm 1130 x 300 x 140

Material AISI 304

Material thickness in mm 0.9

Mounting height in mm 900/700/500

## INTRA PRODUCTS OF STAINLESS STEEL

In order for your Intra stainless steel product AISI304 to retain its original quality and appearance we recommend regular cleaning. Use mild soap or cleaning products specifically designed for stainless steel and clean water. Then wipe the surface with a dry cloth.

Never use detergents containing chlorine, iodine, fluoride or abrasives on stainless steel.

Also avoid contact with acid solutions and other substances incompatible with stainless steel.

Remember that food and skin care products may contain such substances, e.g. ketchup, juice, salt, certain cleansers, nail polish, etc. Promptly remove spills of such products.

Observe the following:

- \* Do not allow water or other liquid to dry in. This is to avoid staining the surface.
- \* Even though stainless steel can withstand harsh treatment, it can easily be scratched by sharp objects. For products with normal, polished (brushed) finish, this will be very visible when the product is new, but after a period of use, this will be negated as the steel loses its lustre. For products with satin and polished finishes, the scratches will always be visible. Never use scouring powder or steel wool on stainless steel. In addition to scratching the steel, wire wool will leave behind small particles that may develop into rust spots which, over time, may corrode the steel.
- \* Stainless steel must not come into contact with, or be in environments containing, chlorine solutions for long periods of time.
- \* Silver polish causes stains which cannot be removed.

# Maintenance P12NFOL

## Maintenance of Intra products in stainless steel

Congratulations on your purchase of an Intra product that has been produced with care and to a high quality. Many of our products are supplied with a plastic film. This film protects the product during the transport and has to be removed before use.

To keep the original quality of your Intra product in AISI304 stainless steel, we recommend regular cleaning. Use washing up liquid and clean water to clean the product after use. Rinse carefully and dry. Don't forget to clean all loose parts, e.g. the drain grating.

Please have the following in mind

- Don't let water or other liquids dry on the product. In this way you avoid that a grey coating builds up on the steel.
- Stainless steel can stand hard treatment but sharp objects can easily scratch the surface. These scratches are more visible when the product is new. After a period of use these

marks will be smoothed out, without the product losing its lustre.

- Never use scouring powder or steel wool to clean the surface. Apart from the risk of scratches, there is also a risk that rust stains will attack the steel.
- Avoid Chlorine based solutions coming into contact with the stainless steel.
- Silver polish leaves spots that cannot be removed.
- Food-stuffs that contain acid or other substances must quickly be removed (e.g. juices, salt, mustard, mayonnaise).

## Discoloration

More stubborn spots are often caused by impurities in the water or household substances. These can be removed with special polish agents for stainless steel. We recommend the use of Intra Shining Kit. Dull spots can become lustrous again if rubbed with chalk on a soft cloth.