










Wash trough P5

Art. no.	P5-FLEX		POLISHED
GTIN	8719585005356		
Art. no.	P5-600		POLISHED
GTIN	8719585005103		
Art. no.	P5-1200		POLISHED
GTIN	8719585005110		
Art. no.	P5-1500		POLISHED
GTIN	8719585005127		
Art. no.	P5-1800		POLISHED
GTIN	8719585005134		
Art. no.	P5-2100		POLISHED
GTIN	8719585005141		
Art. no.	P5-2400		POLISHED
GTIN	8719585005158		
Art. no.	P5-2800		POLISHED
GTIN	8719585005165		
Art. no.	P5-3000		POLISHED
GTIN	8719585005172		
Overall dimension in mm	600-3000 x 474 x 186		
Outlet dimension in mm	1 1/2"		
Material	Stainless steel 18/10, AISI304, 1.4301		
Material thickness in mm	1 / 1,5		
Installation height in mm	500/800/900		



Description

Flexible wash trough supplied with integrated wall brackets.

Inner corners with more than 90° angle, and pressed drain without screws and gasket ensure optimum hygiene and easy cleaning. The sink has a fall against the drain in the center. Soft transitions at all external angles counteract damage in the event of a fall against the trough. Safe and comfortable handle support at the bottom of the edges to prevent injury during assembly. The bowl has enough depth to accommodate a bucket.

Meets all requirements in EN 14296.

Washtroughs available in standard lengths 600, 1200, 1500, 1800, 2100, 2400, 2800 and 3000 mm.

Washtroughs also available in any customer specified length between 600 and 3000. Art. Nr: P5-Flex

