

















Wash trough P9

Art. no.	P9-FLEX		
GTIN	8719585005370		
Art. no.	P9-600		
GTIN	8719585005264		
Art. no.	P9-1200		
GTIN	8719585005271		
Art. no.	P9-1500		
GTIN	8719585005288		
Art. no.	P9-1800		
GTIN	8719585005295		
Art. no.	P9-2100		
GTIN	8719585005301		
Art. no.	P9-2400		
GTIN	8719585005318		
Art. no.	P9-2800		
GTIN	8719585005325		



Overall dimension in mm	600-3000 x 395 x 163
Outlet dimension in mm	1 1/2"
Material	Stainless steel 18/10, AISI304, 1.4301
Material thickness in mm	1 / 1,5
Installation height in mm	500/800/900

Description

Flexible wash trough supplied with integrated wall brackets. Inner corners with more than 90° angle, and pressed drain without screws and gasket ensure optimum hygiene and easy cleaning. The bowl has a fall against the drain in the center. Soft transitions at all external angles counteract damage in the event of a fall against the trough. Safe and comfortable handle support at the bottom of the edges to prevent damage during assembly.

Meets all requirements in EN 14296.

Washtroughs available in standard lengths 600, 1200, 1500, 1800, 2100, 2400, 2800 and 3000 mm.

Washtroughs also available in any customer specified length between 600 and 3000. Art. Nr: P9-Flex

